

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

This Page Blank (uspto)

(21) Application No 9300982.7

(22) Date of filing 19.01.1993

(30) Priority data

(31) 04007855 (32) 20.01.1992 (33) JP

(71) Applicant
NEC Corporation

(Incorporated in Japan)

7-1, Shiba 5-Chome, Minato-Ku, Tokyo 108-01, Japan

(72) Inventor
Mafumi Miyashita

(74) Agent and/or Address for Service
John Orchard & Co
Staple Inn Buildings North, High Holborn, London,
WC1V 7PZ, United Kingdom

(51) INT CL⁶
G08B 7/06, H04B 5/04

(52) UK CL (Edition L)
G4H HRCU H1A H13D H14A H14B H14G H60
U1S S2196 S2213


(56) Documents cited
None

(58) Field of search
UK CL (Edition L) **G4H HRCU**
INT CL⁶ **G08B, H04B**

(54) Paging receiver

(57) A paging receiver has a conversion table 38 for storing plural canned messages. When a space data is included in one of certain positions in a received signal, data preceding the space data is determined as a conversion code. The conversion code is converted to a corresponding canned message using the conversion table 38. Information including the canned message, and a general message following the space data in the received signal, is displayed.

FIG. 2



At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

This print takes account of replacement documents submitted after the date of filing to enable the application to comply with the formal requirements of the Patents Rules 1990.

FIG. 1




FIG. 2




FIG. 3




FIG. 4

TRANSMISSION REQUEST DATA

1	2
---	---

RECEIVED DATA

1	2	┐	┐	┐
---	---	---	---	---

SPACE

DISPLAYED MESSAGE

0	1	2	3	—	4	5	—	6	7	8	9	┐
---	---	---	---	---	---	---	---	---	---	---	---	---

PAGING RECEIVER

This invention relates to a paging receiver,
5 and more particularly, to a paging receiver with a display function.

A recent paging receiver is provided with a
10 display function to show a received message such as a telephone number of the caller, a telephone number of a voice mail, etc.

A first conventional paging receiver includes
a display device which displays all content of a
15 received message directly. According to the paging receiver, however, there is a disadvantage in that it takes a long time to transmit a long message from a transmitter like a telephone set.

A second conventional paging receiver is
20 provided with a conversion table storing plural kinds of canned messages. One type of the second conventional paging receiver includes a detector for detecting a predetermined code in a received signal. In the paging receiver, data following the detected
25 code is converted to a corresponding canned message stored in the conversion table, and the canned message

is displayed.

Another type of the second conventional paging receiver includes a detector for detecting a specific code in a received signal. In the paging receiver, operation mode changes to a conversion mode when the specific code is detected thereby. In the conversion mode, the received signal is converted to a corresponding canned message.

According to the second conventional paging receiver, however, there is a disadvantage in that the received signal is complicated to be converted to a canned message, so that the paging receiver becomes impractical.

A third conventional paging receiver includes a conversion circuit for converting a word data of the first figure in a received signal to canned message corresponding to the word data. Then, the canned message is displayed. According to the third conventional paging receiver, however, there is a disadvantage in that a general message can not be displayed when the canned message is displayed.

A feature of one paging receiver to be described is that a conversion code can be converted to a corresponding canned message

easily, despite that both of a canned message and a general message can be displayed at the same time.

In one embodiment to be described, a paging receiver includes:

- 5 means for receiving a transmitted signal to provide a received signal, the received signal including a selective call signal and a message signal, the message signal being of plural figures and including a conversion code and a space code;
- 10 means for comparing the selective call signal to an identification number of the paging receiver to provide a coincidence signal, when the selective call signal is identical to the identification number;
- means for storing message at addresses
15 corresponding to conversion codes;
- means for checking the message signal as to whether the space code is detected in a predetermined figure among the plural figures, when the coincidence signal is generated;
- 20 means for accessing to the storing means to read a message corresponding to the conversion code of the message signal in the received signal, when the space code is detected in the predetermined figure; and
- means for displaying the message read by the
25 accessing means.

An embodiment of the invention will

now be described, by way of example, with reference to the accompanying drawings, in which:-

5

Fig. 1 is a block diagram showing a paging receiver of a preferred embodiment,

10 Figs. 2 and 4 are schematic views used for explaining operation of the preferred embodiment, respectively, and

Fig. 3 is a flow chart showing operation of the first preferred embodiment.

15

Fig. 1 shows a paging receiver of a preferred embodiment according to the invention, which receives a signal transmitted from a paging transmitter. The paging receiver includes a control unit 10, an antenna 12 for receiving a transmitted signal including a call signal and a message signal, a keyboard 14 connected to the control unit 10 for supplying a predetermined data thereto, a receiving circuit 16 connected to the antenna 12, an ID-ROM 18 connected to the control unit 10, a message storing memory 20 connected to the control unit 10, a driver 22 connected to the control

20

25

unit 10, an information device 24 connected to the driver to be driven thereby, and a display 26 connected to the driver 22 to be driven thereby.

5 The receiving circuit 16 demodulates a signal modulated on a carrier signal supplied from the antenna 12 to a call signal and a message signal. The ID-ROM 18 stores a conversion table 38 shown in Fig. 2, a predetermined program and an ID number for the paging receiver. Such information stored in the ID-ROM may be
10 modified and new information may be added thereto by an operator using the keyboard 14.

The control unit 10 includes a control circuit 30 connected to the keyboard 14, the ID-ROM 18, the message storing memory 20 and the driver 22 to
15 control them, respectively, a comparator 32 connected to the receiving circuit 16 and the control circuit 30, and a space detector 34 connected to the control circuit 30.

The comparator 32 compares a call number
20 included in a received signal to the ID number stored in the ID-ROM, and supplies a coincidence signal to the control circuit 30 when the received call number is coincident to the ID number. The space detector 34 detects whether a space data is present in the first
25 three figures of a received data D_m.

The conversion table 38 stored in the ID-ROM

18 includes plural kinds of canned messages
corresponding to a plurality of conversion codes.

Next, operation of the preferred embodiment
will be explained in conjunction with Figs. 2 and 3.

5 When a message signal is transmitted from paging
transmitter, the signal is received at the antenna 12
of the paging receiver. Part of the received signal is
shown in Fig. 2 as a message signal including a
conversion code "12", a space data "_", and a general
10 message "01", which are generated by pressing key
buttons of the transmitter, for example, the space data
is generated by pressing buttons of an asterisk "*" and
"2". The message signal is generated by CCIR (Comité
Consulatif International des Radiocommunications) No.1
15 as one block having five figures each having four bits.

When the transmitted signal is received at
the antenna 12, the received signal is supplied to the
receiving circuit 16, and the received signal is
demodulated to provide a call signal and the above
20 described message signal. Then, the modulated signal
is supplied to the comparator 32, and the call signal
is compared to the ID number stored in the ID-ROM 18.
At this time, if the call signal is coincident to the
ID number, a coincidence signal is supplied to the
25 control circuit 30.

When the coincidence signal is supplied to

the control circuit 30, the space data of the third figure in the message data D_m is checked by the space detector 34. When it is detected that the space data is present therein, data "12" preceding the space data is determined as a conversion code and data following the space data "01" is determined as general message, respectively. If a space data is not detected by the space detector 34, all message data is determined as general message.

10 In response to the conversion code "12", a canned message "0123-45-6789" corresponding to the conversion code "12" is read from the conversion table 38 of the ID-ROM 18 by the control circuit 30. The canned message "0123-45-6789" is combined with the
15 general message "01" to generate a complete message "0123-45-6789_01", and the complete message "0123-45-6789_01" is supplied to the message storing memory 20 to be stored therein.

After that, the complete message "0123-45-
20 6789_01" is supplied from the message storing memory 20 through the control circuit 30 to the driver 22. Then, the message is supplied to the display 26 and the information circuit 24, so that the message "0123-45-6789_01" is displayed by the display 26 and a
25 predetermined alarm is generated by the information circuit 24.

Otherwise, if the received data includes no conversion code, or the conversion table 38 does not have data corresponding to the conversion code, the received data is displayed directly without conversion by the display 26.

In Fig. 3, a second figure ($I=2$) of a received signal is checked as to whether the figure is a space code or not. When the figure is the space code, the above described conversion sequence starts to provide a converted message. On the other hand, when the figure is not the space data, a third figure ($I=I+1$) of the received signal is checked in the same manner, so that the same control is carried out. Here, if it is assumed that a number "n" is 3, a fourth figure of the received data is no longer checked, because the relation of " $I < n+1$ " is not met.

Fig. 5 shows another case in which a transmitting data includes only a conversion code "12" therein. When only a conversion code "12" is instructed to be transmitted in a transmitter (not shown), a signal of "12____" is generated therein to be transmitted to the paging receiver.

In the receiver, the first space data next to "2" is detected by the space detector 34, so that data "12" is determined as a conversion data. Therefore, only canned message "0123-45-6789" corresponding to the

conversion code "12" is displayed by the display 26.

Although the invention has been described
with respect to specific embodiment for complete and
clear disclosure, the appended claims are not to be
5 thus limited but are to be construed as embodying all
modification and alternative constructions that may be
occur to one skilled in the art which fairly fall
within the scope of the claims.

CLAIMS

1. A paging receiver, comprising:

means for receiving a transmitted signal to provide a received signal, said received signal including a selective call signal and a message signal, said message signal being of plural figures and including a conversion code and a space code;

means for comparing said selective call signal to an identification number of said paging receiver to provide a coincidence signal, when said selective call signal is identical to said identification number;

means for storing message at addresses corresponding to conversion codes;

means for checking said message signal as to whether said space code is detected in a predetermined figure among said plural figures, when said coincidence signal is generated;

means for accessing to said storing means to read a message corresponding to said conversion code of said message signal in said received signal, when said space code is detected in said predetermined figure; and

means for displaying said message read by said accessing means.

2. A paging receiver, according to claim 1,
wherein:

said receiving means receives said
transmitted signals to provide said received signal
5 including said selective call signal and said message
signal, said message signal including said conversion
code, said space code, and a general code; and

said displaying means displays said message
and information of said general code.

3. A paging receiver, according to claim 1,
wherein:

said checking means checks a second figure of
said message signal to detect said space code, and a
5 predetermined number of figures following said second
figure of said message signal subsequently until said
space code is detected when said second figure is not
said space code.

4. A paging receiver, comprising:

means for storing plural canned messages
corresponding to conversion codes;

5 means for detecting a space data in one of
first predetermined figures in a received signal;

means for determining data preceding a

detected space data as a conversion code and data following said detected space data as a general message;

10 means for reading a message corresponding to said conversion code from said plural canned messages in said storing means; and

means for displaying information which includes said canned message and said general message.

5. A paging receiver, according to claim 4, wherein:

said conversion code, said canned message and said general message are numerical data.

6. A paging receiver as claimed in claim 1 substantially as described herein with reference to the accompanying drawings.

- 13 -

Patents Act 1977
Examiner's report to the Comptroller under
Section 17 (The Search Report)

Application number

GB 9300982.7

Relevant Technical fields

(i) UK CI (Edition L) G4H (HRCU)

(ii) Int CI (Edition 5) G08B, H04B

Databases (see over)

(i) UK Patent Office

(ii)

Search Examiner

M J DAVIS

Date of Search

24 MARCH 1993

Documents considered relevant following a search in respect of claims 1-6

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
	NONE	

Category	Identity of document and relevant passages	Relevant to claim(s)

Categories of documents

X: Document indicating lack of novelty or of inventive step.

Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.

A: Document indicating technological background and/or state of the art.

P: Document published on or after the declared priority date but before the filing date of the present application.

E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.

&: Member of the same patent family, corresponding document.

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).

This Page Blank (uspto)